







Product Ordering Part Number

Part Number	Product	Description	Image
VACSYS-MCU-V30	Vacuum Controller and Data Acquisition System, Version 3.0	Micro-Controller Unit, Version 3.0 - Monitors up to 100 vacuum cups per unit. - 4-digit LCD display, one LED indicator, two push buttons, one built-in loud buzzer (80db @ 1 ft), a 12VDC rechargeable battery and an AC charger. - 1x built-in USB data port - Built-in software allowing user to program alarm trigger level and data sampling rate	
VACSYS-CBL- X VSNSR X: Number of Sensors	Data Cable	4-wire Data Cable - Length varies based on track design - 1x per track, connects up to 25 vacuum sensors	
VACSYS-VSNSR-T	Vacuum Sensor	Vacuum Sensor - 0-30 inHg, - with a quick-disconnect T-fitting - 1x per vacuum cup.	
VACSYS-PS-60PSI	Pressure Switch	System On/Off Pressure Switch - 60 psi (Rising), Normal Open, 1/4" NPT Male Connector - 1x per Flex Rail System.	

Additional Accessories/ Spare Parts:

Part Number	Product	Description	Image
VACSYS-12VBAT	Battery	12VDC, 8000 mA Li-Ion Rechargeable Battery w/ LED Capacity Indicator and Quick Connector	
VACSYS-12VBATRAY	Battery Holder	Battery holder with two Velcro tapes	
VACSYS-12VBATCHG	Battery Charger	Battery Charging Power Adaptor Input: AC 100-240V, 50/60Hz, 2A Output: DC 5V	